

Modular Keystone 24 Copper Frame



Features

- Modular design, models accommodate up to 24 UTP or STP keystone-type jacks in 1U
- Simple assembly and installation, jacks are terminated separately and then mounted onto the panel
- Models incorporating Category 8, Cat 6A, Cat 6 & Cat 5e Jacks
- Transparent labels holders
- Different jacks may be mixed on the same panel

Cat 6A

- Cat 6A STP Patch Panels featuring Category 6A performance. The system is designed to ANSI/TIA/EIA-568-2.D , ISO/IEC 11801 2.1 edition and CENELEC EN50173 (200x) for Category 6A/CLASS E_A .
- The system is designed to support protocols running at up to IEEE 802.3an 10Gbps, 1000 Mbps, such as ATM 622 Mbps and Gigabit Ethernet.

Cat 6

- Cat 6 Jacks are part of the featuring Category 6 performance. The system is designed to conform to ANSI/TIA/EIA-568-2.D, ISO/IEC 11801 2nd edition (2002) and CENELEC EN50173 (2002) for Category 6/Class E.

Specifications

- **Capacity:** Accepts up to 24 Jacks.
- **Cable Clamping:** Cable retention tray enhances cable strain relief
- **Material:** Aluminum
- **Colors:** Black background with gray silk-screened markings
- **Standards:** Conforms to IEC-60603-7 (603-7) for keystone-type, snap-on apertures



Modular Keystone 24 Copper Frame

Physical : 24 Ports

Height	44.4 mm / 1.75" (1U)
Width	482.6 mm / 19"
Tray	105 mm (4.13")
Weight	0.35 kg (0.73 lb)
Weight with Cable Retention	
Tray	0.33 kg (0.73 lb)

Ordering Information

Number	Description
GCUPPUS1UXXXX	Genuis Patch Panel 24 port UTP Straight Unloaded 1U
GCUPPSS1UXXXX	Genuis Patch Panel 24 port STP Straight Unloaded 1U